

Control your servers from a compact 1U rack-mount console

Unique single-rail system offers a compact LCD console with high-quality video and laptop-style keyboard



The Belkin LCD Rack Console enables system administrators to conveniently control racked servers from a single, secure, compact console. With its slim design, the Rack Console fits a standard 19-inch rack, ensuring clearance for the full extension of the LCD and keyboard.

Its unique single-rail system lets the LCD panel slide easily from the server rack. The Rack Console offers other advanced features such as a key-locking mechanism to prevent unauthorized access, and cable-management arms that organize console cables as the drawer extends and retracts. Available in 17-inch colour displays, or 17-inch LCD Rack Consoles with Built-In KVM Switch. The LCD Rack Consoles are excellent solutions for server administrators.

Benefits


Rack Console

- Features grade-A, 17" LCD, TFT, active-matrix colour panel for high-quality images, especially for viewing multiple applications
- Delivers 1280x1024@65Hz resolution through a protected, tempered-glass overlay for best visual performance
- Features single-rail design to enhance sliding performance and save rack space
- Integrates compact 106-key function keyboard, including numeric 10-key pad with centrally located touch pad for optimal ergonomics
- Features adjustable brackets for broadest rack compatibility and ease of installation

Rack Console with Built-In KVM Switch

- Available in 17" LCD TFT, active-matrix colour panel for best visual performance
- Belkin PRO3 technology supports a combination of PS/2 and USB servers
- Graphical On-Screen Display (OSD) allows easy access to your servers
- Daisy-chain capability allows you to control up to 256 servers with Belkin PRO3 KVM Switches

1U Rack Console



Check out these Belkin KVM products to go with your Rack Console:

Perfect addition to your Rack Consoles with Built-In PRO3 KVM



OmniView® SMB Remote IP Device (F1DP101Mea)
Adds IP control to your KVM switch



OmniView PRO3 USB & PS/2 KVM Switch
4-Port Switch (F1DA104Zea)
8-Port Switch (F1DA108Zea)
16-Port Switch (F1DA116Zea)
Daisy-chain to add KVM ports to your console

Consider the following KVM products from Belkin for your Rack Console:



OmniView SMB KVM-over-IP Switch
8-Port Switch (F1DP108Gea)
16-Port Switch (F1DP116Gea)



OmniView SMB CAT5 KVM Switch
4-Port Switch (F1DP104Aea)
8-Port Switch (F1DP108Aea)
16-Port Switch (F1DP116Aea)

Package Contents

Rack Console

- 17" LCD Rack Console
- Power Cable
- VGA, PS/2 Cable Kit
- Bracket Kit
- Console Screws
- Quick Installation Guide

Rack Console

- 17" LCD Rack Console with Built-In KVM Switch
- Flash Cable
- Bracket Kit
- Console Screws
- Quick Installation Guide & Manual

Product Specifications

Part Number:	F1DC101PxxSR	F1DC108BxxSR	F1DC116BxxSR
Enclosure:	Heavy-duty steel	Heavy-duty steel	Heavy-duty steel
Power:	Auto-switching 100 to 240VAC 50 to 60Hz 48 watts	External power brick	External power brick
Dimensions:	19 (W) x 21.7 (D) x 1.70 (H) in. (482.6 x 551.2 x 43.18mm)	17.5 (W) x 23.5 (D) x 1.75 (H) in. (444.5 x 597 x 44.5mm)	17.5 (W) x 23.5 (D) x 1.75 (H) in. (444.5 x 597 x 44.5mm)
Weight:	26.9 lbs. (12.2kg.)	33.0 lbs. (15.0kg.)	34.1 lbs. (15.5 kg.)

Console Specifications

Display Type:	17 in. LCD active-matrix colour	17 in. LCD active-matrix colour	17 in. LCD active-matrix colour
Resolution:	Up to 1280x1024	Up to 1280x1024	Up to 1280x1024
Contrast Ratio:	450:1	450:1	450:1
Brightness:	250 cd/m2 typical	250 cd/m2 typical	250 cd/m2 typical
Pixel Pitch:	0.264mm x 0.264mm	0.264mm x 0.264mm	0.264mm x 0.264mm
Panel Colour:	16.7 million display colours	16.7 million display colours	16.7 million display colours
Viewing Angle:	115 degrees	115 degrees	115 degrees
Response Time:	Rising 2ms, decay 14ms	Rising 2ms, decay 14ms	Rising 2ms, decay 14ms
Keyboard/Mouse Type:	Laptop-style, integrated, high-quality keyboard with touch pad	Laptop-style, integrated, high-quality keyboard with touch pad	Laptop-style, integrated, high-quality keyboard with touch pad
Operating Life of Individual Keys:	8 million cycles	8 million cycles	8 million cycles

CPU/Other KVM Specifications

CPU/CPU/KVM Ports:	1	8	16
CPU/KVM Video Connection:	VGA	VGA	VGA
CPU/KVM Keyboard/Mouse Connection:	PS/2	PS/2, USB	PS/2, USB

Warranty 2 years

Note: The Rack-Mount Console is available with multiple keyboard layouts.

Part Number

F1DC101PxxSR
F1DC108BxxSR
F1DC116BxxSR

Description

17" LCD Rack Console
LCD Rack Console with Built-In 8-port KVM
LCD Rack Console with Built-In 16-port KVM