



Specification :

1. Connector Type : SC/PC Singlemode.
2. Cable Marker.
3. Cable Type :
Zipcord cable, $\varnothing 3.0\text{mm}$, $8.3/125\mu\text{m}$ Singlemode.
Cable Jacket : Yellow color, PVC material.
4. Shrink Tube.
5. Length : xM.

Performance :

- a. Insertion Loss : $< 0.3 \text{ dB}$.
- b. Return Loss : $> 40 \text{ dB}$.
- c. Fiber Extension : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$.
- d. Ferrule End-face Radius : $10 < R < 25\text{mm}$.
- e. Apex Offset : $< 50\mu\text{m}$.
- f. Increase in insertion loss after 500 mating : 0.2 dB Max .
- g. Operation Temperature : -20°C to $+70^{\circ}\text{C}$.
- h. Storage Temperature : -40°C to $+80^{\circ}\text{C}$.
- i. Humidity (non-condensing) $95\% \text{RH}$.

BELKIN®

BELKIN CORPORATION
501 West Walnut Street, Compton, CA 90220-5221, USA
TEL: 310-898-1100; FAX: 310-898-1111
www.belkin.com

PART NO.: F2F80277

DES.: SC to SC Duplex patch cord