



Specification :

1. Connector Type : LC/PC Singlemode.
2. Connector Type : ST/PC Singlemode.
3. Cable Type :
Zipcord cable, $\varnothing 3.0\text{mm}$, 8.3/125um Singlemode.
Cable Jacket : Yellow color, PVC material.
4. Cable Marker.
5. Shrink Tube.
6. Length : xM.

Performance :

- a. Insertion Loss : $< 0.3 \text{ dB}$.
- b. Return Loss : $> 40 \text{ dB}$.
- c. Fiber Extention : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$.
- d. Ferrule End-face Radius : $10 < R < 25\text{mm}$.
- e. Apex Offset : $< 50\mu\text{m}$.
- f. Increase in insertion loss after 500 mating : 0.2 dB Max.
- g. Operation Temperature : -20°C to $+70^{\circ}\text{C}$.
- h. Storage Temperature : -40°C to $+80^{\circ}\text{C}$.
- i. Humidity (non-condensing) 95%RH.

BELKIN®

BELKIN CORPORATION
 501 West Walnut Street, Compton, CA 90220-5221, USA
 TEL: 310-898-1100; FAX: 310-898-1111
 www.belkin.com

PART NO.: F2F802L0

DES.: ST to LC Duplex patch cord