

Pro Series Non-IEEE 1284 Parallel Extension Cable - 1.8m - F3D112b06

The Extension Cable Straight-through, 25 Conductor is most commonly used to extend the length of an existing DB25 cable assembly, but it can also be used as a PC to serial modem cable.



©2000 Belkin Components

Product Features:

- State-of-the-art wiring design ensures 100% compatibility with all devices 100% of the time.
- Oversized ergonomic thumbscrews make installation a breeze.
- The Belkin Lifetime Warranty.
- 28 AWG stranded tinned copper conductors are individually insulated in polypropylene to minimize cross talk, ensuring high-speed, error-free transmission.
- PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress.
- Gold plated copper contacts provide maximum conductivity and keep data loss to a minimum.
- Flextec® PVC rubberized cable jacket is extremely flexible for use in tight areas.
- Molded strain relief and PVC overmolding to ensure a lifetime of error-free data transmission.
- Ground indents provide excellent conductivity and retention with mating conductors.
- Aluminum undermold shielding helps to meet FCC requirements on EMI/RFI interference.
- Without Retail Packaging

Belkin Ltd
Rushden
United Kingdom

Belkin BV
Schiphol-Rijk
Netherlands

Belkin GmbH
Munich
Germany

Belkin SAS
Billancourt
France

Belkin Nordic
Stockholm
Sweden