

## Gold Series VGA Monitor Signal Replacement Cable - 1.8m(6 feet) - F2N028-06-GLD

Designed to interface any PC compatible computer to a VGA or SVGA monitor with HDBB15 female connectors. Featuring 24K gold plated corrosion-proof connectors for maximum conductivity.



©2008 Belkin Components

### Características del producto:

- 24K gold plated corrosion-proof connectors for maximum conductivity.
- Tactilite®: molded strain relief provides a 360-degree turning radius for true protection against damage to the conductors.
- Flextec®: cable jacket is very durable and extremely flexible for use in tight areas.
- Quality assured with the Belkin Lifetime Warranty.
- Tactilite®: overmold is a supple polymer designed to increase flexibility while maintaining durability.
- 24K gold plated copper contacts provide maximum conductivity with no data loss.
- Fastest data transfer for maximum performance.
- Oversized ergonomic thumbscrews make installation a breeze.
- Ground indents provide excellent conductivity and retention with mating conductors.
- PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress.
- Aluminum undermold shield helps to meet FCC requirements on EMI/RFI interference.
- Low capacitance impedance matched 28 AWG stranded tinned copper conductors are individually insulated in polypropylene to minimize cross talk, ensuring high-speed, error-free transmission.

Belkin Ltd  
Rushden  
Reino Unido

Belkin BV  
Schiphol-Rijk  
Países Bajos

Belkin GmbH  
Munich  
Alemania

Belkin SAS  
Biliacourt  
Francia

Belkin Nordic  
Stockholm  
Suecia