

SCSI III Ultra Fast and Wide Cable with Thumbscrews - 1.8Metre(6 foot) - F2N1066-06-T

Used to interface any two SCSI devices such as a scanner and CD-ROM, wherein one has an Ultra Micro Centronics 68 female port and the other has a Micro DB68 Female port.



©2000 Belkin Components

Características del producto:

- Rated for SCSI III applications.
- Double shielded (braid and foil) to meet SCSI specifications and ensure compliance with FCC requirements reducing EMI/RFI interference.
- Low-capacitance impedance matched 28 AWG stranded tinned copper are individually insulated in polypropylene.
- Thumbscrews enable easy installation.
- Full lifetime warranty.
- 25 or 34 tightly woven conductor pairs ensures that each data line is paired with a ground line to minimize interference ensuring error-free data transmissions.
- State-of-the-art wiring design ensures 100% compatibility.
- Gold plated copper contacts for a clean, clear transmission.
- PVC premold encapsulates individual conductors to eliminate stress.
- Flextec® trade: PVC rubberized cable jacket is extremely flexible for use in tight areas.
- Aluminum undermold shield helps meet FCC requirements.
- Ground indents provide excellent conductivity and retention with mating connector.

Belkin Ltd
Rushden
Reino Unido

Belkin BV
Schiphol-Rijk
Países Bajos

Belkin GmbH
Munich
Alemania

Belkin SAS
Billancourt
Francia

Belkin Nordic
Stockholm
Suecia