

Pro Series Non-IEEE 1284 Parallel Switchbox Cable - 3M (10 feet) - CC3008aed10

The Pro Series 25-Conductor, Straight-through Cable Assembly is most commonly used in applications with manual and automatic switchboxes. Featuring our exclusive wiring design and cable technology that guarantees optimal performance.



©2008 Belkin Components

Product Features:

- State-of-the-art wiring design ensures 100% compatibility with all devices 100% of the time.
- Oversized ergonomic thumbscrews make installation a breeze.
- Gold plated copper contacts provide maximum conductivity and keep data loss to a minimum.
- The Belkin Lifetime Warranty.
- Flextec® 153; PVC rubberized cable jacket is extremely flexible for use in tight areas.
- Low capacitance impedance matched 28 AWG stranded tinned copper conductors are individually insulated in polypropylene to minimize cross talk, ensuring high-speed, error-free transmission.
- PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress.
- Double shielded braid to ensure compliance with FCC requirements and reducing EMI/RFI.
- Molded strain relief and PVC overmolding to ensure a lifetime of error-free data transmission.
- Ground indents provide excellent conductivity and retention with mating conductors.
- Aluminum undermold shielding helps to meet FCC requirements on EMI/RFI interference.
- 28 AWG stranded tinned copper PVC insulated conductors for excellent signal transmission.
- *Without Retail Packaging*

Belkin Ltd
Rushden
United Kingdom

Belkin BV
Schiphol-Rijk
Netherlands

Belkin GmbH
Munich
Germany

Belkin SAS
Billancourt
France

Belkin Nordic
Stockholm
Sweden